



APPLICATIONS

Featuring an input voltage range from 90V to 253V AC and four stabilised outputs, EMTrust's 3U, 12TE CompactPCI power supply units comply to the CompactPCI specification and are also available for extended operating temperature range.

- ▶ Rugged Embedded Systems
- ▶ Instrumentation
- ▶ Robotics
- ▶ Industrial Control and Automation
- ▶ Maintenance-Free Systems
- ▶ Traffic and Transportation
- ▶ Measurement & Control

ICP-PSU-AC120

120W Modular AC/DC Power Supply Unit



ICP-PSU-AC120

FEATURES

- ▶ Dedicated CompactPCI PSU
- ▶ 120W continuous load output
- ▶ Fully protected stabilized outputs
- ▶ Automatic failure recovery
- ▶ EMI filtered
- ▶ Full safety compliance
- ▶ LED status and power indication

BENEFITS

- ▶ Open standard architecture
- ▶ Service & user friendly
- ▶ 19" cassette for improved maintenance
- ▶ Long-term product availability





ICP-PSU-AC120

PSU

OVERVIEW

All outputs are individually protected against overload, short circuits and over temperature conditions, and are capable of automatic recovery once the fault condition is rectified.

The PSU is designed for compliance with EN60950 safety standards, and can deliver up to 120W output at environmental temperatures up to 50°C.

SPECIFICATION SUMMARY

- ▶ 4 regulated DC outputs
- ▶ Fully protected
- ▶ Active cooling
- ▶ Status LEDs
- ▶ Extended operational temperature
- ▶ High MTBF
- ▶ Rugged 3U cPCI format

SPECIFICATIONS

INPUT VOLTAGES RANGE Between 90V AC and 253V AC	COMPATIBILITY Compatible with EMTrust PSU	MASS 1.25kg
FUSE 2.5AT (external)	STANDBY-POWER 10W	OPERATING TEMP -10°C to +70°C (derating >50°C)
INPUT FREQ. 48Hz to 62Hz	POWER 120W @ +50°C; derating by 2%/K t > 50°C	EXTENDED TEMP -25°C to +85°C (derating >50°C)
OUTPUT <ul style="list-style-type: none"> ▶ Ua1 +3.3V, 10A with 11A current limit ▶ Ua2 +5.1V @ 15A with 16A current limit ▶ Ua3 +12V @ 1A with fixed limiting at 1.8A ▶ Ua4 -12V @ 0.25A with fixed limiting at 1.8A 	EFFICIENCY >80% (typ.) at max. load	STORAGE TEMP -25°C to +85°C
POWER FAIL Open-collector; active low at Ua2 ≤ 4.90V	CONNECTOR DIN EN 60603 (DIN 41612) M-connector	CLIMATIC CLASS EN60654-1 Class B2
TURN-ON < 1000ms	STATUS LEDS +3.3V, +5.0V, +/-12.0V (green) Standby (yellow)	HUMIDITY 5% to 95% (non-condensing) @ 40°C
PROTECTION Continuous short-circuit protection. Overvoltage monitoring (and limiting) of 3.3V line to avoid incorrectly keyed 3.3V/5.0V CompactPCI backplane	INHIBIT According to CompactPCI specification	SAFETY <ul style="list-style-type: none"> ▶ EN60950 ▶ Protection Class I ▶ Overvoltage Category II ▶ Pollution Degree 2
	ENABLE FUNCTION According to CompactPCI specification	EMISSION <ul style="list-style-type: none"> ▶ EN55022 Limit A ▶ EN61000-3-2
	COOLING Thermostat regulated fan unit (internal)	IMMUNITY <ul style="list-style-type: none"> ▶ EN 61000-6-2 ▶ EN 61000-4-2 ▶ EN 61000-4-4 ▶ EN 61000-4-5

ORDERING INFORMATION

PRODUCT	DESCRIPTION
ICP-PSU-AC120-t	3U, 120W, AC/DC stabilised, switched-mode PSU with M power connector and 3 outputs (+12V, +5V and +3.3V)
KEY:	t- Temp. Range 0 = 0°C to +70°C (1 = -25°C to +85°C) - Contact Sales



EMTrust GmbH Headquarters
Gewerbering 1
85258 Weichs
Germany

Tel.: +49 8136 80 677-800
Fax: +49 8136 80 677-809
sales@emtrust.de
www.emtrust.de

EMTrust GmbH Office Kempten
Poststrasse 27
87439 Kempten
Germany

Tel.: +49 831 5753389-51
Fax: +49 831 5753389-99
sales@emtrust.de
www.emtrust.de

Trucomp, Inc.

11555 Heron Bay Blvd
Suite 200
Coral Springs, FL 33076, USA

Phone +1 954 603-0582
Fax +1 954 603-0581
sales@trucompusa.com
www.trucompusa.com

The information contained in this document has been carefully checked and is believed to be reliable. However, EMTrust GmbH makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of what ever nature resulting from the use of, or reliance upon, it. EMTrust does not guarantee that the use of any information contained herein will not infringe upon the patent, trademark, copyright or other rights of third parties, and no patent or other license is implied hereby. Intel and Intel logo are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

This document does not in any way extend EMTrust's warranty on any product beyond that set forth in its standard terms and conditions of sale. EMTrust reserves the right to make changes in the products or specifications, or both, presented in this publication at any time and without notice.

LIFE SUPPORT APPLICATIONS

EMTrust's products are not intended for use as critical components in life support appliances, devices or systems in which the failure of a EMTrust product to perform could be expected to result in personal injury. All mentioned trademarks are registered trademarks of their owner.

© 2011 EMTrust GmbH. All rights reserved. Rev. 1.3 / 21.09.2011